

Art	Verschiebung	Förderleistung		Druck	Max. Umdrehungen	Abmessungen			
		@ 1500 U / min	@ max. U / min			P _{nom}	n	EIN	B
	cm ³ / Umdrehung	l / min	l / min	Bar	U / min	mm	mm	G	G
10A (C) 1X053G	1	1.4	3.26	250	3500	39.1	81	G 3/8 - A	G 3/8 - A
10A (C) 1.25X053G	1.25	1.74	4.07	250	3500	39.5	82		
10A (C) 1.6X053G	1.6	2.23	5.21	250	3500	40.3	83.6		
10A (C) 2X053G	2	2.82	6.58	250	3500	41.1	85.2		
10A (C) 2.5X053G	2.5	3.53	8.23	250	3500	42.1	87.2		
10A (C) 2.65X053G	2.65	3.74	8.72	250	3500	42.4	87.8		
10A (C) 3.15X053G	3.15	4.44	10.36	250	3500	43.5	89.8	G 1/2 - A	
10A (C) 3,65X053G	3.65	5.15	12.01	250	3500	44.4	91.9		
10A (C) 4.2X053G	4.2	5.92	13.82	250	3500	45.5	94.1		
10A (C) 4.7X053G	4.7	6.63	15.46	250	3500	46.1	96		
10A (C) 5X053G	5	7,05	14.10	250	3000	47.1	97.2		
10A (C) 5.7X053G	5.7	8.12	16.25	200	3000	48.5	100.1		
10A (C) 6.1X053G	6.1	8.69	14.49	200	2500	49.4	101.8		
10A (C) 7.4X053G	7.4	10.55	17.58	180	2500	52.1	107.2		
10A (C) 8X053G	8	11.4	15.2	150	2000	53.4	109.7		
10A (C) 8.5X053G	8.5	12.11	16.15 Uhr	150	2000	54.4	111.7		
10A (C) 9.8X053G	9.8	13.97	18.62	120	2000	57	117		

